

| 1300 SERIES | | | | |
|----------------------------------|----------|-----------|-----------|----------|
| Model Number | 1300 | 1300-HYDG | 1300-HGI | 1300-9G |
| Head Bore | 8-1/4" | 8-1/4" | 8-1/4" | 9-1/8" |
| Pressure Rating (Static/Dynamic) | 1000/500 | 1000/500 | 2000/1500 | 1000/500 |
| RPM (max) | 200 | 200 | 200 | 200 |
| Lubricated | ✓ | na | na | na |
| Sealed | na | ✓ | ✓ | ✓ |
| Manual Clamp | ✓ | na | na | ✓ |
| Hydraulic Clamp | na | ✓ | ✓ | na |
| 1024 Thread On Element* | ✓ | ✓ | ✓ | na |
| 1510 Thread On Element* | na | na | na | ✓ |

* Available in Natural Rubber or Urethane both with various bore sizes



| 1400 SERIES | | | |
|------------------------------------|----------|-----------|-----------|
| Model Number | 1400 | 1400-HYDG | 1400-HGI |
| Head Bore | 8-1/4" | 8-1/4" | 8-1/4" |
| Pressure Rating (Static/Dynamic) | 1000/500 | 1000/500 | 2000/1500 |
| RPM (max) | 200 | 200 | 200 |
| Lubricated | ✓ | na | na |
| Sealed | na | ✓ | ✓ |
| Manual Clamp | ✓ | na | na |
| Hydraulic Clamp | na | ✓ | ✓ |
| 4010 Bolt On Element* | ✓ | ✓ | ✓ |
| Adapter for 1024 Thread on Element | Optional | Optional | Optional |
| Kelly Drive | Optional | Optional | Optional |

* Available in Natural Rubber or Urethane both with various bore sizes



| 1360 STRIPPER-TUBING HEAD (NON ROTATING) | |
|--|------------------|
| Model Number | 1360 |
| Bore (Pass Thru) | 7" to 10-3/4" |
| Pressure Rating (Static) | 3500 |
| RPM (max) | 200 |
| Manual Clamp | ✓ |
| 9010 Element* (TUBING SIZE) | 1-1/2" TO 5-1/2" |

* Available in Natural Rubber or Urethane both with various bore sizes

